

## MONNELI EPOFLOOR LM UV

*Two Components Line Marking Polyurethane Coating for Traffic*

### Product Description

---

A specially formulated fast drying line marking paint that can be applied in one coat for marking lines on concrete, epoxy or polyurethane surfaces. Epofloor LM UV paint is based on Polyurethane

### Uses

---

EPOFLOOR LM-UV is used:

- As a line marking paint with Epofloor range of products or car park deck coating systems.
- General epoxy and polyurethane coated decks
- Car park flooring
- Concrete surface in factories, warehouses and car parks
- Playground and sport flooring
- Kerb stones and stair, treads

### Advantages

---

- Suitable for exterior and interior applications
- Quick drying
- Excellent resistance against water, oil, alkalis and hydrocarbon fuels
- Good adhesion to concrete, epoxy and polyurethane coatings
- Durable with excellent abrasion resistance
- Good reflection properties when mixed with glass beads

### Instructions for Use

---

#### Surface Preparation

The surface should be sound, clean, dry and free from loose material, laitance, dirt, oil, grease or any other contaminants. If needed, wash the surface with detergent and then with clean water. Allow to dry completely before application. Do not use solvent to clean the surface before applying the product.

#### Application

Epofloor LM UV can be applied with brush, roller or airless spray gun. If airless spray gun is used. The nozzle tip of the gun should be from 4-6 mm. Apply the paint with a pressure of 30-40 psi.

Apply Epofloor LM UV at a rate of 5m<sup>2</sup>/Liter (200 microns wet). If another coat is needed to build up the thickness, then apply the second coat after the first one is totally dry.

For the light reflection, proper glass beads with size <200 microns can be sprinkled on top of the applied coating while it is still wet.

#### Cleaning

Clean tools with Solvente 10 promptly before material hardens. Cured material must be mechanically removed.

## Technical Data

Properties	Results
Appearance	Liquid
Color	5 Colors: 1023 3020 5017 6024 9016
Mix density at 25°C	1.45 kg /L
Solid content	65%
Touch dry at 25°C	3 hours
Application temperature	5°C to 35°C
Recommended minimum dry film thickness	150 microns

All values are subject to 5-10 % tolerance

### Mixing

Mix the contents of the container thoroughly for 1 minute before application. Do not add any kind of solvents.

### Packaging

Product	Pack Size	Coverage
Epopfloor LM UV	4 Liter	5-6m <sup>2</sup> / Liter

Stated consumptions data are for general guidance.

Actual consumption depends on the nature of substrate, method of application and wastage.

In case of use of antislip aggregates, the consumption values for the top coat will be reduced by 15 - 20%.

## Storage

Original sealed kit of Epofloor LM UV has a shelf life of 12 months provided it is stored clear of ground in a dry and shaded place below 35°C.

Keep the product in tightly closed containers stored in dry covered place, at a temperature not less than +5°C and not more than +35°C. Under these conditions, the product will have a shelf life of 12 months.

## Limitations

Do not apply the paint during rainy or stormy weather or when humidity is greater than 80%.

## Health & Safety

During application, wear appropriate protective clothing, goggles, gloves and respiratory equipment if necessary. In case of contact with skin, rinse with water and again wash thoroughly with soap and water. In case of contact with eyes, rinse with plenty of water and seek medical advice accordingly.

If ingested, obtain medical attention immediately. Do not induce vomiting.

The information in this Technical Data Sheet is based on Colmef Monnelli's experience. Colmef Monnelli does not accept any liability arising from the use of its products as it has no direct or continuous control over where or how its products are applied. All Colmef Monnelli's Data Sheets are updated on regular basis. It is the user's responsibility to obtain the latest version.

DUBAI  
ABU DHABI  
KSA  
ITALY

P.O. Box 123808 Dubai UAE  
P.O. Box 127326 Abu Dhabi, UAE  
P.O. Box 335896 Code: 11383 - Riyadh KSA  
Z.I. Ponte d'Assi 06024 Gubbio (PG)

T. +971 4 8803488 F. +971 4 8803450  
T. +971 2 5511949 F. +971 2 5511749  
T. +966 1 2654277 F. +966 1 2654335  
T. +39 75 9221297 F. +39 75 9221174

**EPOFLOOR LM UV**  
Technical Data Sheet  
Edition: January 2020  
Revision: 02

[colmef@colmef.ae](mailto:colmef@colmef.ae)

[www.colmef-me.com](http://www.colmef-me.com)